



Parameter	Value	Units
Rated voltage	12	VDC
Operating Voltage	1.5 - 16	VDC
Rated Current @ 12 VDC	8 Max.	mA
Sound Pressure Level @12 VDC @30 cm.	80 Min.	dBA
Frequency	4.0 +/- 0.5	KHz.
Operating Temp.	-30 to +80	°C
Storage Temp.	-40 to +120	°C
Weight	2	Grams



Transducers USA
 1400 Howard Street
 Elk Grove, IL 60007
 Toll Free: 800-956-1920 FAX: 847-956-1950
www.tusainc.com info@tusainc.com

All dimensions are in MM unless otherwise specified

Drawing Number:

TRIP-1412S

Title:

PIEZO AUDIO INDICATOR

Date:

6_20_2004

THE INFORMATION DISCLOSED HEREIN WAS ORIGINATED BY AND IS THE PROPERTY OF TRANSDUCERS USA, INC. AND EXCEPT FOR USE EXPRESSLY GRANTED TO THE UNITED STATES GOVERNMENT, TRANSDUCERS USA, INC. RESERVES ALL PATENT PROPRIETARY DESIGN, USE, SALE, MANUFACTURING AND PRODUCTION RIGHTS THERE TO. THIS DOES NOT APPLY TO VENDOR