


SCOPE: This specification applies to TRTE-1205P(G)

SPECIFICATIONS:


Type	
Rated Voltage (V)	5
Operating Voltage (V)	3~7
Rated Current (MA)	< 40
Coil Resistance (ohm)	45 ± 5
Coil Impedance (ohm)	80
Sound Output at 10cm (dB)	> 85
Resonant Frequency (Hz)	2400
Operating Temperature (C)	-25 ~ +70
Storage Temperature (C)	-30 ~ +85
Weight (g)	2

Value applying rated voltage (2400Hz, 1/2duty, square wave)

DIMENSIONS Unit:mm Tolerance:±0.5



Transducers USA
Confidential and Proprietary



Transducers USA
1400 Howard Street
Elk Grove, IL 60007
Toll Free: 888-921-6400 FAX: 847-956-1950
www.tusainc.com info@tusainc.com

All dimensions are in MM unless otherwise specified

Drawing Number:

TRTE-1205P(G)

E/M Audio Buzzer

Date:

1/30/2018

THE INFORMATION DISCLOSED HEREIN WAS ORIGINATED BY AND IS THE PROPERTY OF TRANSDUCERS USA, INC. AND EXCEPT FOR USE EXPRESSLY GRANTED TO THE UNITED STATES GOVERNMENT TRANSDUCERS USA, INC. RESERVES ALL PATENT PROPRIETARY DESIGN, USE, SALE, MANUFACTURING AND PRODUCTION RIGHTS THERETO. THIS DOES NOT APPLY TO VENDOR